

Industrial Power Supply

Features

- ▶ I/P Voltage range: 80-135Vac or 180-265Vac; 90-110Vdc
- ▶ Leakage current < 10 mA
- ▶ With power good and fail signal output
- ▶ Fixed switching frequency at 100KHz
- ▶ Redundant: Two units of same type can be operated in parallel into a redundant system
- ▶ Protection: SCP/OVP/OCP/OTP
- ▶ 2 years warranty



| Model No. | Input Power (Vac/Hz) | Output Voltage/Current (Vdc/Amps) | Output Power(W) | Dimension L*W*H (mm) |
|------------|---------------------------------|-----------------------------------|-----------------|----------------------|
| PC-FP01 | 90~132Vac/47~63Hz | 24Vdc/0~30A | 720W+720W | 482.6*300*133.2 |
| PC-FP01A | 185~260Vac/47~63Hz | 24Vdc/0~30A | 720W+720W | 482.6*300*133.2 |
| PC-FP04 | 90~132Vac or 185~260Vac/47~63Hz | 24Vdc/0~35A | 840W+840W | 482.6*300*133.2 |
| PC-FP03 | 90~132Vac/47~63Hz | 24Vdc/0~42A | 1000W+1000W | 482.6*300*133.2 |
| PC-FP04-3C | 90~264Vac/47~63Hz | 24Vdc/0~35A | 840W+840W | 482.6*300*133.2 |

| Model No. | Input Power (Vdc) | Output Voltage/Current (Vdc/Amps) | Output Power(W) | Dimension L*W*H (mm) |
|-----------|-------------------|-----------------------------------|-----------------|----------------------|
| PC-FP06 | 90~110Vdc | 24Vdc/0~21A | 500W+500W | 482.6*300*133.2 |

